



## VAC150G Specifications

### Standard Equipment

- 31 HP V-Twin B&S Gas Engine
- 450 CFM Lobe Type Blower @ 14" Hg. Continuous With Simultaneous 3.8 GPM @ 2000 PSI Water Flow – Giant High Pressure Water Pump with Electric Clutch
- Y-Strainer Water Filter Element
- 95 Gallon Plastic Fresh Water Tank with 1-½" Drain Valve
- 6 Gallon Anti-Freeze Tank With 1" PVC 3-Way Valve
- Low Water Automatic Engine Shutdown
- Caterpillar Pressure Sensitive Regulating Unloader Valve
- Large Blower Silencer Muffler For Noise Abatement - 80 db.
- 130 Gallon Spoils Tank With 6" Full Spoils Tank Check Valve And 3" Inlet Gate Valve
- Hydraulic Full Opening Rear Door Cammed For Using A Single Handle, Moving 4 Deadbolts Into Lock Position And A 3" Drain Gate Valve
- 5 Micron Washable Bag Filtration, Wet Or Dry Vacuum Capability With 3" PVC Drain Valve
- 10 Gallon Fuel Cell
- 6000# Torflex Rubber Torsion Axle With Electric Brakes
- (2) ST235/80 R16 Load Range E Tires
- Rear Curbside Aux. Hydraulics – 10 GPM @ 3000 PSI With 10 Gallon Oil Reservoir
- Oil Reservoir
- Lockable Hose Reel With 50' HP Hose & Flexible Spray Wand
- 2" Vacuum Relief Valve
- 2-½" Stainless Steel Vacuum Gauge
- 7000# Trailer Jack
- 12-Volt Battery
- Curbside Controls
- 2-5/16" Ball Hitch. Pintle Hitch Available Upon Request
- 3" X 25' Vac Hose With Ball And Socket Fittings
- 16" Lawn Sweep On 3" Steel Vac Tube
- Standard Valve Box Cleanout Tool
- Strobe & Dual Halogen Work Light Kit

### Dimensions

- Skid Mount: Fits In 8' (96") Truck Bed
- Trailer Mount:
  - Width – 6'7" (79")
  - Length – 15' (180")
  - Height – Approx. 7'2" (86") - Top of Strobe